POMECO 100 Counterweight Hose Retractors

POMECO 100 Counterweight Hose Retractors keep excess hose off the ground and out of the way, prolonging hose life and reducing potential hazards. The POMECO 100 is a California Air Resources Board (CARB) certified Stage II component for use with single and dual hose dispensers as per Executive Order G-70-52-AM.



Features

- Easy to Use counterweights are precisely matched to each hose configuration to ensure that a minimal pulling force is needed throughout hose extension.
- Easy to Maintain the 100 has just two moving parts, ensuring a long service life with a minimum of maintenance.
- Multiple Hose Configurations the 100 is available in a multitude of configurations to meet virtually any conventional or vapor recovery hose/nozzle configuration. Models are also available for air and water hose applications to keep hoses clear of vehicles when not in use.

Ordering Specifications

Conventional and Vapor Recovery Applications

Model # Hose Configuration Hose Length ft. m in. mm in. mm in. mm in. cm lbs. kg 6100-4000 Conventional 12-14 3.7-4.3 13/6 35 1 25 79 201 33 15.0 6100-5000 Conventional 15-18 4.6-5.5 13/8 35 1 25 92 234 38 17.2 6100-6000 Conventional 12-14 3.7-4.3 11/32 26 3/8 or 3/4 16 or 19 79 201 30 13.6 6100-7000 Conventional 15-20 4.6-6.1 11/32 26 3/8 or 3/4 16 or 19 92 234 31 14.1 6100-8000 Conventional 12-14 3.7-4.3 1 25 3/8 16 79 201 29 13.2 6100-9000 Conventional 15-20 4.6-6.1 1 25 3/8 16 92 234 30 13.6 6100-AGNV Inverted Coaxial 11-13 3.4-4.0 (Hose Clamp Not Included) 79 201 33 15.0
6100-4000 Conventional 12-14 3.7-4.3 1% 35 1 25 79 201 33 15.0 6100-5000 Conventional 15-18 4.6-5.5 1½ 35 1 25 92 234 38 17.2 6100-6000 Conventional 12-14 3.7-4.3 1½ 26 ½ or ¾ 16 or 19 79 201 30 13.6 6100-7000 Conventional 15-20 4.6-6.1 1½ 26 ½ or ¾ 16 or 19 92 234 31 14.1 6100-8000 Conventional 12-14 3.7-4.3 1 25 ½ 16 79 201 29 13.2 6100-9000 Conventional 15-20 4.6-6.1 1 25 ½ 16 92 234 30 13.6
6100-5000 Conventional 15-18 4.6 - 5.5 13/8 35 1 25 92 234 38 17.2 6100-6000 Conventional 12-14 3.7 - 4.3 11/32 26 5/8 or 3/4 16 or 19 79 201 30 13.6 6100-7000 Conventional 15-20 4.6 - 6.1 11/32 26 5/8 or 3/4 16 or 19 92 234 31 14.1 6100-8000 Conventional 12-14 3.7 - 4.3 1 25 5/8 16 79 201 29 13.2 6100-9000 Conventional 15-20 4.6 - 6.1 1 25 5/8 16 92 234 30 13.6
6100-6000 Conventional 12-14 3.7 - 4.3 1½2 26 5% or ¾ 16 or 19 79 201 30 13.6 6100-7000 Conventional 15-20 4.6 - 6.1 1⅓2 26 5% or ¾ 16 or 19 92 234 31 14.1 6100-8000 Conventional 12-14 3.7 - 4.3 1 25 5% 16 79 201 29 13.2 6100-9000 Conventional 15-20 4.6 - 6.1 1 25 5% 16 92 234 30 13.6
6100-7000 Conventional 15-20 4.6 - 6.1 1½2 26 5% or ¾ 16 or 19 92 234 31 14.1 6100-8000 Conventional 12-14 3.7 - 4.3 1 25 5% 16 79 201 29 13.2 6100-9000 Conventional 15-20 4.6 - 6.1 1 25 5% 16 92 234 30 13.6
6100-8000 Conventional 12-14 3.7 - 4.3 1 25
6100-9000 Conventional 15-20 4.6 - 6.1 1 25 1/8 16 92 234 30 13.6
6100-AGNV Inverted Coaxial 11-13 3.4 - 4.0 (Hose Clamp Not Included) 79 201 33 15.0
6100-AGLC Coaxial 11-13 3.4 - 4.0 (Hose Clamp Not Included) 79 201 26 11.8
6100-AGBR Coaxial w/ Breakaway 11-13 3.4 - 4.0 (Hose Clamp Not Included) 79 201 31 14.1

100 Series Counterweight Hose Retractor Instruction Sheet Order Number: **H15852PA**

See page 198 for hose clamp Ordering Specifications

NOTE: See OPW's Website at www.opwglobal.com for product instruction sheets, trouble-shooting guides, how-to-use guide and to view the Do's & Don'ts at the Gas Pump video.

Options and Replacement Parts

Description	Counterweight Length		Weight	
	in.	cm	lbs.	kg
Counterweight for 4000/ AGNV Models	27	68.5	24	10.8
Counterweight for 5000 Model	31	78.7	27	12.2
Counterweight for 6000, 8000 and AGLC Models	20	50.8	17	7.7
Counterweight for 7000, 9000, AGBR Models	25	63.5	22	9.9
Sliding Bracket, Dispenser Mount				
Replacement Tube, 2" x 2" x 75" (191 cm)				
Replacement Tube, 2" x 2" x 88" (224 cm)				
	Counterweight for 4000/ AGNV Models Counterweight for 5000 Model Counterweight for 6000, 8000 and AGLC Models Counterweight for 7000, 9000, AGBR Models Sliding Bracket, Dispenser M Replacement Tube, 2" x 2"	DescriptionLet in.Counterweight for 4000/AGNV Models27Counterweight for 5000 Model31Counterweight for 6000, 8000 and AGLC Models20Counterweight for 7000, 9000, AGBR Models25Sliding Bracket, Dispenser MountReplacement Tube, 2" x 2" x 75" (19	Counterweight for 4000/ AGNV Models Counterweight for 5000 Model Counterweight for 6000, 8000 and AGLC Models Counterweight for 7000, 9000, AGBR Models Sliding Bracket, Dispenser Mount Replacement Tube, 2" x 2" x 75" (191 cm)	Description Length in. cm lbs. Counterweight for 4000/ AGNV Models Counterweight for 5000 Model Counterweight for 6000, 8000 and AGLC Models Counterweight for 7000, 9000, AGBR Models Sliding Bracket, Dispenser Mount Replacement Tube, 2" x 2" x 75" (191 cm)

Part #	Description
D02671M	Replacement Housing, Plastic
H15266	Top and Pulley Assembly
H15264	12 ft. Replacement Cable
C05239M	Retractor Foot
P100-4STF	Freestanding Retractor Base
P338SPOOL	Replacement Cable Spool, 338 ft. of wire
H15210M	Cable Guide
H13588M	Retaining Ring