



ITEM NO.	QTY	PART NAME	A-208-W		A-209-W		A-209-W-MO	
			MATERIAL	PART NO.	MATERIAL	PART NO.	MATERIAL	PART NO.
1	1	BODY	STEEL	208-1-CS	STAINLESS	209-1-SS	CF8M STAINLESS	209-1-MO
2	1	SPRING	STAINLESS	205-2-MO	STAINLESS	205-2-MO	STAINLESS	205-2-MO
3	1	SPRING SEAT	STAINLESS	207-3-SS	STAINLESS	207-3-SS	STAINLESS	207-3-SS
4	3	LOCK NUT	STEEL	205-4-CS	STAINLESS	207-4-SS	STAINLESS	207-41-SS
5	1	STEM	STAINLESS	207-5-SS	STAINLESS	207-5-SS	STAINLESS	207-5-MO
6	1	PRESSURE SEAL	BUNA-N ⁽¹⁾	205-6-BN	BUNA-N ⁽¹⁾	205-6-BN	BUNA-N ⁽¹⁾	205-6-BN
7	1	WEATHER CAP	STAINLESS	205-7-SS	STAINLESS	205-7-SS	STAINLESS	205-7-SS
8	1	NAMEPLATE	STAINLESS	209-87-SS	STAINLESS	209-87-SS	STAINLESS	209-87-SS

NOTE: 1 Alternate material available

Standard minimum start to discharge pressure setting is 0.75 PSI vacuum.
Alternate start to discharge pressure settings are available.

Net flow area: 1.12 square inches