



MODEL	DESCRIPTION
ST-48-DA	Pneumatic Actuator, Double Acting - 482 Inch Pounds Force at 80 PSI Open and Close
ST-48-SR6	Pneumatic Actuator, Spring Return - (264 Inch Pounds Force at 80 PSI Open, 296 Inch Pounds Force Spring Close)
ST-75-DA	Pneumatic Actuator, Double Acting - Recommended for 2"-4" Valves. (738 Inch Pounds Force at 80 PSI Open and Close)
ST-75-SR5	Pneumatic Actuator, Spring Return - Recommended for 2"-3" Valves. (464 Inch Pounds Force at 80 PSI Open, 392 Inch Pounds Force Spring Close)
ST-75-SR6	Pneumatic Actuator, Spring Return - Recommended for 2"-3" Valves. (411 Inch Pounds Force at 80 PSI Open, 470 Inch Pounds Force Spring Close)
ST-105-DA	Pneumatic Actuator, Double Acting - Recommended for 4"-5" Valves. (1088 Inch Pounds Force at 80 PSI Open and Close)
ST-105-SR5	Pneumatic Actuator, Spring Return - Recommended for 2"-3" Valves. (684 Inch Pounds Force at 80 PSI Open, 585 Inch Pounds Force Spring Close)
ST-105-SR5-P	Pneumatic Actuator, Spring Return Perpendicular Setup - Recommended for 2"-3" Valves. (684 Inch Pounds Force at 80 PSI Open, 585 Inch Pounds Force Spring Close)
ST-157-DA	Pneumatic Actuator, Double Acting - Recommended for 5"-6" Valves. (1574 Inch Pounds Force at 80 PSI Open and Close)
ST-157-SR5	Pneumatic Actuator, Spring Return - Recommended for 4" Valves. (1025 Inch Pounds Force at 80 PSI Open, 838 Inch Pounds Force Spring Close)
ST-157-SR5-P	Pneumatic Actuator, Spring Return Perpendicular Setup - Recommended for 4" Valves. (1025 Inch Pounds Force at 80 PSI Open, 838 Inch Pounds Force Spring Close)
ST-157-SR6	Pneumatic Actuator, Spring Return - Recommended for 4" Valves. (919 Inch Pounds Force at 80 PSI Open, 1006 Inch Pounds Force Spring Close)
ST-237-DA	Pneumatic Actuator, Double Acting - Recommended for 6" Valves. (2379 Inch Pounds Force at 80 PSI Open and Close)
ST-237-SR5	Pneumatic Actuator, Spring Return - Recommended for 5"-6" Valves. (1496 Inch Pounds Force at 80 PSI Open, 1339 Inch Pounds Force Spring Close)
ST-237-SR5-P	Pneumatic Actuator, Spring Return Perpendicular Setup - Recommended for 5"-6" Valves. (1496 Inch Pounds Force at 80 PSI Open, 1339 Inch Pounds Force Spring Close)
ST-331-DA	Pneumatic Actuator, Double Acting - Recommended for 6"-12" Valves. (3316 Inch Pounds Force at 80 PSI Open and Close)
ST-331-SR5	Pneumatic Actuator, Spring Return - Recommended for 6" Valves. (2222 Inch Pounds Force at 80 PSI Open, 1879 Inch Pounds Force Spring Close)
ST-406-DA	Pneumatic Actuator, Double Acting - Recommended for 8" - 12" Valves. (4069 Inch Pounds Force at 80 PSI Open and Close)
ST-U75-SR5	Pneumatic Actuator, Spring Return ISO Mounting - Recommended for 2"-3" Valves. (464 Inch Pounds Force at 80 PSI Open, 392 Inch Pounds Force Spring Close)
ST-U75-SR6	Pneumatic Actuator, Spring Return ISO Mounting - Recommended for 2"-3" Valves. (411 Inch Pounds Force at 80 PSI Open, 470 Inch Pounds Force Spring Close)
ST-U105-SR5	Pneumatic Actuator, Spring Return ISO Mounting - Recommended for 2"-3" Valves. (684 Inch Pounds Force at 80 PSI Open, 585 Inch Pounds Force Spring Close)
ST-U157-SR5	Pneumatic Actuator, Spring Return ISO Mounting - Recommended for 4" Valves. (1025 Inch Pounds Force at 80 PSI Open, 838 Inch Pounds Force Spring Close)
ST-U406-DA	Pneumatic Actuator, Double Acting ISO Mounting - Recommended for 8" - 12" Valves. (4069 Inch Pounds Force at 80 PSI Open and Close)
ST-U406-SR5	Pneumatic Actuator, Spring Return ISO Mounting - Recommended for 5" - 6" Valves. (2622 Inch Pounds Force at 80 PSI Open, 2192 Inch Pounds Force Spring Close)