POMECO 100 Counterweight Hose Retractors

POMECO 100 Counterweight Hose Retractors keep excess hose off the ground and out of the way, prolonging hose life and reducing potential hazards. The POMECO 100 is a California Air Resources Board (CARB) certified Stage II component for use with single and dual hose dispensers as per Executive Order G-70-52-AM.

Materials Housing: Impact-resistant plastic Cable: Black polyester Post: Aluminum (2"x 2") Retractor Foot Top and Pulley Housing Hose Clamp Post 2" x 2" Sliding Bracket

Features

- Easy to Use counterweights are precisely matched to each hose configuration to ensure that a minimal pulling force is needed throughout hose extension.
- Easy to Maintain the 100 has just two moving parts, ensuring a long service life with a minimum of maintenance.
- Multiple Hose Configurations the 100 is available in a multitude of configurations to meet virtually any conventional or vapor recovery hose/nozzle configuration. Models are also available for air and water hose applications to keep hoses clear of vehicles when not in use.

Ordering Specifications

Conventional and Vapor Recovery Applications

6100-5000 Conventional 15-18 4.6 - 5.5 13% 35 1 25 92 234 38 6100-6000 Conventional 12-14 3.7 - 4.3 1½2 26 % or ¾ 16 or 19 79 201 30 6100-7000 Conventional 15-20 4.6 - 6.1 1½2 26 % or ¾ 16 or 19 92 234 31 6100-8000 Conventional 12-14 3.7 - 4.3 1 25 % 01 79 201 29	Model #	Hose Configuration	Hose	Length		Hose O.D. Hose I.D.		Height		Weight		
6100-5000 Conventional 15-18 4.6 - 5.5 13/6 35 1 25 92 234 38 6100-6000 Conventional 12-14 3.7 - 4.3 11/32 26 5/6 or 3/4 16 or 19 79 201 30 6100-7000 Conventional 15-20 4.6 - 6.1 11/32 26 5/6 or 3/4 16 or 19 92 234 31 6100-8000 Conventional 12-14 3.7 - 4.3 1 25 5/6 16 79 201 29			ft.	m	in.	mm	in.	mm	in.	cm	lbs.	kg
6100-6000 Conventional 12-14 3.7 - 4.3 1½2 26 5% or ¾ 16 or 19 79 201 30 6100-7000 Conventional 15-20 4.6 - 6.1 1½2 26 5% or ¾ 16 or 19 92 234 31 6100-8000 Conventional 12-14 3.7 - 4.3 1 25 5% 16 79 201 29	6100-4000	Conventional	12-14	3.7- 4.3	13/8	35	1	25	79	201	33	15.0
6100-7000 Conventional 15-20 4.6 - 6.1 11/32 26 5/6 or 3/4 16 or 19 92 234 31 6100-8000 Conventional 12-14 3.7 - 4.3 1 25 5/6 16 79 201 29	6100-5000	Conventional	15-18	4.6 - 5.5	1¾	35	1	25	92	234	38	17.2
6100-8000 Conventional 12-14 3.7 - 4.3 1 25 5/8 16 79 201 29	6100-6000	Conventional	12-14	3.7 - 4.3	1 1/32	26	5/8 or 3/4	16 or 19	79	201	30	13.6
	6100-7000	Conventional	15-20	4.6 - 6.1	1 1/32	26	5/8 or 3/4	16 or 19	92	234	31	14.1
6100-9000 Conventional 15-20 4.6 - 6.1 1 25 1/8 16 92 234 30	6100-8000	Conventional	12-14	3.7 - 4.3	1	25	5/8	16	79	201	29	13.2
	6100-9000	Conventional	15-20	4.6 - 6.1	1	25	5/8	16	92	234	30	13.6
6100-AGNV Inverted Coaxial 11-13 3.4 - 4.0 (Hose Clamp Not Included) 79 201 33	6100-AGNV	Inverted Coaxial	11-13	3.4 - 4.0	(Hose Clamp Not Included)			79	201	33	15.0	
6100-AGLC Coaxial 11-13 3.4 - 4.0 (Hose Clamp Not Included) 79 201 26	6100-AGLC	Coaxial	11-13	3.4 - 4.0	(Hos	(Hose Clamp Not Included) 79			201	26	11.8	
6100-AGBR Coaxial w/ Breakaway 11-13 3.4 - 4.0 (Hose Clamp Not Included) 79 201 31	6100-AGBR	Coaxial w/ Breakaway	11-13	3.4 - 4.0	(Hose Clamp Not Included)			79	201	31	14.1	

100 Series Counterweight Hose Retractor Instruction Sheet Order Number: **H15852PA**

See page 199 for hose clamp Ordering Specifications

NOTE: See OPW's Website at www.opwglobal.com for product instruction sheets, trouble-shooting guides, how-to-use guide and to view the Do's & Don'ts at the Gas Pump video.

Options and Replacement Parts

Part #	Description		rweight ngth	Weight		
	- a.a., p	in.	cm	lbs.	kg	
H15262	Counterweight for 4000/ AGNV Models	27	68.5	24	10.8	
H15263	Counterweight for 5000 Model	31	78.7	27	12.2	
H15260	Counterweight for 6000, 8000 and AGLC Models	20	50.8	17	7.7	
H15261	Counterweight for 7000, 9000, AGBR Models	25	63.5	22	9.9	
H15265M	Sliding Bracket, Dispenser M	lount				
C05235M	Replacement Tube, 2" x 2" x 75" (191 cm)					
C05236M	Replacement Tube, 2" x 2" x 88" (224 cm)					

Part #	Description
D02671M	Replacement Housing, Plastic
H15266	Top and Pulley Assembly
H15264	12 ft. Replacement Cable
C05239M	Retractor Foot
P100-4STF	Freestanding Retractor Base
P338SPOOL	Replacement Cable Spool, 338 ft. of wire
H15210M	Cable Guide
H13588M	Retaining Ring