## **Materials**

Packing & Disc: Fluorocarbon Lever & Lever Guard: Duratuff® Spout: Stainless steel O.D. 19mm (0.75 in) per ISO 22241 Specifications Inlet Size: 3/4" NPT or 3/4" BSPP

Weight: 2.73 lbs. each, 43.1 lbs./case of 15, 1.25 kg each, 19.9 kg/case of 15

## **Features - Benefits**

- Lowest Overall Cost of Ownership reliable, long lasting design based on proven OPW quality platform and industry standard-setting technology
- DEF Compatible all materials of construction are 100% 3rd party tested and approved for DEF compatibility
- Ease of Use sleek, lightweight design with patented Accu-Stop<sup>®</sup>
  Flow Control Technology and convenient one-finger hold-open clip to set flow rate
- ◆ User Comfort attractive 2-Piece NEWGARD<sup>™</sup> Hand Insulator is the most comfortable nozzle in the industry in hot or cold weather

- Vehicle Protection our Duratuff<sup>®</sup> lever guard not only provides for rugged durability when dropped but also won't scratch your fleet vehicle
- Meets ISO 22241 Requirements

## **Design Working Pressure**

• 50 PSI (3.45 bar) maximum pressure

NOTE: The OPW 19DEF Series Nozzles are for commercial fleet applications only and are not UL Listed for gasoline dispensing facilities.

## **OPW 19DEF Series Industrial Automatic Nozzle**

When you're responsible for ensuring the safe, reliable and affordable dispensing of Diesel Exhaust Fluid (DEF) for on-road, off-road, commercial and industrial heavy-duty trucks, farming or other diesel powered vehicles, you rely on the most trusted name in dispensing nozzles – OPW.

As the global standard for more than a century, OPW nozzles are built to perform better and last longer\* than any other brand to deliver unprecedented peace-of-mind, ROI, and performance. The NEW OPW 19DEF Series Industrial Automatic Nozzle is specifically designed for your commercial and industrial fleet operations, offering unmatched reliability with the features you want.

\* OPW internal lab cycle testing results with DEF as of August 2013.

<b>•</b>				
Ord	lering	Spec	'ITICA'	tions
	<u>.</u>			

Product #	Description	
19DEF-0500SS	Nozzle - 19mm spout; $3\!\!4$ " Female NPT inlet connection, blue hand warmer	
19DEF-050LSS	Nozzle - 19mm spout; $3\!4$ " Female BSPP inlet connection, blue hand warmer	
Hose Adaptors	(Sold Separately).	
19DM-0100	$3\!$	
19DF-0100	34" MNPT to 1 "FNPT - Connecting nozzle to 1 " NPT Male hose	
19DML-0100	¾" MBSPP to 1" MBSPP - Connecting nozzle to 1" BSPP Female hose	
19DML-0075	34" MBSPP to $34$ " MBSPP - Connecting nozzle to $34$ " BSPP Female hose	
-		