

Quick Bolt-On Couplings

Easy to install and maintain, the QBC Quick Bolt-On Double Wall Pipe Coupling gives users the same great features as our SBC bolt-on double-wall fittings and reduces NPT threaded connections within a piping system. The QBC features a face with an embedded gasket that clamps easily to a flat face, creating a fluid and vapor-tight seal.

The QBC is compatible with OPW C15A (1.5") and C20A (2") product pipe, as well as V20 (2") vent pipe.

Utilize the QBC inside dispenser, tank or transition sumps.

Made of stainless-steel, it can be used with all fuel types and DEF.



Features & Benefits:

- ◆ All Stainless-Steel Wetted Surfaces
- ◆ No Jacket Stripping
- ◆ No Test Boots
- ◆ No Pipe Thread Sealant
- ◆ Unique quick connection face/ fitting that completely encapsulates the sealing gasket; only available through OPW
- ◆ State-of-the-art clamshell interlock design only available through OPW
- ◆ Extreme-Cold (XC) gasket available
- ◆ UL Listed for all fuel types

Quick Bolt-On Coupling Ordering Specifications

Part #	Description
QBC-2150	Quick Connect to Male Barb 1.5"
QBC-2200	Quick Connect to Male Barb 2.0"
QBC-2150XC	Quick Connect to Male Barb 1.5", XC
QBC-2200XC	Quick Connect to Male Barb 2.0", XC
QNA-2150F	1.5" Male NPT to Quick Connect, Flat Face
QNA-2200F	2.0" Male NPT to Quick Connect, Flat Face
QTF-2215	Quick Connect Tee, 1.5" NPT
QEF-2015	Quick Connect Elbow, 1.5" NPT
QCC-2000	Clamp, Quick Connect Coupling
QGC-2000	Clamp/Gasket Kit
QGC-2000XC	Clamp/Gasket Kit, Extreme Cold
QGP-2000XC	Gasket Pack, 2.0" Extreme Cold
QGP-2000	Gasket Pack, 2.0"
QF-TOOL	Installation Tool, QBC

