

SPECIFICATIONS

Physical Configurations:

3-Nozzle/30 HP -

One DryLite AirCannon dryer centered on the Head Beam and one DryLite AirCannon dryer on each Leg Assembly.

Tunnel Space Required	5' with silencers 6'
Unit Height	11' with silencers 11'
Unit Width	13' 8" with silencers 13' 8"
Vehicle Height Clearance	7' 5" approximately

4-Nozzle/40 HP -

Two DryLite AirCannon dryers centered on the Head Beam and one DryLite AirCannon dryer on each Leg Assembly.

Tunnel Space Required	5' with silencers 6'
Unit Height	11' with silencers 11'
Unit Width	13' 8" with silencers 13' 8"
Vehicle Height Clearance	7' 5" approximately

4-Nozzle/40 HP -

Two DryLite AirCannon dryers centered on the Head Beam and one DryLite SideKick dryer on each Leg Assembly.

Tunnel Space Required	5' with silencers 6'
Unit Height	11' with silencers 11'
Unit Width	13' 8" with silencers 13' 8"
Vehicle Height Clearance	7' 5" approximately

5-Nozzle/50 HP -

Three DryLite AirCannon dryers centered on the Head Beam and one DryLite SideKick dryer on each Leg Assembly.

Tunnel Space Required	5' with silencers 6'
Unit Height	11' with silencers 11'
Unit Width	13' 8" with silencers 13' 8"
Vehicle Height Clearance	7' 5" approximately

Utility Requirements:

208V	90 FLA
230V	84 FLA
460V	42 FLA



208V	120 FLA
230V	112 FLA
460V	56 FLA



208V	120 FLA
230V	112 FLA
460V	56 FLA



208V	150 FLA
230V	140 FLA
460V	70 FLA



- 3-Nozzle/30 HP and 4-Nozzle/40 HP dryers are available in floor mount and wall mount frame designs.
- Many additional dryer configurations available.
- AirCannon and SideKick dryers are also available without lights; and come in multiple solid color options to match your brand.

Belanger
1001 Doheny Court
P.O. Box 5470
Northville, MI 48167-5470 USA
belangerinc.com | 248-349-7010

BELANGER 

PART OF

OPW 
VEHICLE WASH
SOLUTIONS
a **DOVER** company