

Whisper Wheel®



Designed as a dedicated horizontal surface washer, the Whisper Wheel® excels at cleaning hoods, roofs and trunk lids – all while providing a super-quiet customer experience. The uniquely shaped Neotex™ closed-cell foam wash 'fingers' provide superior wash penetration with vastly reduced in-car noise levels.

To deliver consistent cleaning results, regardless of vehicle size or shape, the Whisper Wheel® features one of the industry's highest pivot points, along with a fully adjustable counterweight. This allows it to glide over customer vehicles with just the right pressure – maximizing cleaning effectiveness and safety.

Because the Whisper Wheel® is a key contributor in achieving a clean car, it's built for maximum uptime and dependable operation. The fully-boxed 'I-Beam' aluminum frame is corrosion-free, rigid and strong. The sealed automotive-grade bearings are 'greased for life' and require zero maintenance.

When used with a Belanger controller, the available Auto-Retract option automatically senses open truck beds and safely lifts out of the way. This can make the Whisper Wheel® a smart choice for operators who want the benefits of a top wash wheel that actively accomodates every vehicle.



Belanger Incorporated Products Specification Sheet



Belanger, Inc. reserves the right to revise specifications, features or designs, and to change or discontinue models at any time without notice or obligation. Prices subject to change without notice.

BE0102

Copyright 2012
Belanger, Inc.



Whisper Wheel®

REQUIREMENTS

Physical

Tunnel Space Required	114"
Unit Height	140"
Unit Width	146"
Vehicle Height Clearance	90"



Utilities

Hydraulic Drive Option:

Electrical Requirements	3 Phase, 2HP Motor (optional) 110 VAC for Auto Retract option <i>(with Belanger tunnel controller only)</i>
Hydraulic Requirements	6 GPM @ 900 PSI
Pneumatic Requirements	.3 CFM @ 90 PSI minimum & 120 PSI maximum
Water Requirements	3/4" Feed @ 4 GPM @ 40 PSI

Electric Drive Option:

Electrical Requirements	1HP, 3-Phase, 208/240/480 VAC 110 VAC for Auto Retract option <i>(with Belanger tunnel controller only)</i>
Pneumatic Requirements	.3 CFM @ 90 PSI minimum & 120 PSI maximum
Water Requirements	3/4" Feed @ 4 GPM @ 40 PSI

COLOR OPTIONS

Choose from two vivid
Whisper Wheel® colors

