

# Civacon Model 8030 Ground Verification Monitor from OPW-ES

The Model 8030 has been designed to allow the rack operator to visually confirm when a ground connection between the transport and the loading terminal has been achieved, resulting in increased safety and operational peace-of-mind while confirming rack-equipment integrity when a trailer won't load.



## FEATURES & BENEFITS

- Compatible with most loading terminal ground schemes
- Easy to install and use
- Chassis is contained in a small explosion-proof enclosure
- Automatically operates via connections to the transport
- Lightweight: 13 lbs (6 kg)
- LED lamps for long life and reliability
  - 100,000-hour minimum

## ALSO AVAILABLE

### Grounding Cables & Clamp



7720-7720  
(Straight Cord)

OR



7720-COIL  
(Coiled Cord)



Junction Box 7500-7500

## SPECIFICATIONS

|  |
|--|
| <b>Product #:</b> 8030-120 (120V) · 8030-240 (240V)  |
| <b>Operating Temperature:</b> -40°F to 140°F (-40°C to 60°C)   |
| <b>Input Requirements:</b> 120VAC 60 Hz, 10 VA (Standard) – 240VAC version available – please inquire        |
| <b>Output Relay Contacts:</b> 240VAC – 5A  |
| <b>Electrical Connections:</b> Internal terminal strips  |
| <b>Enclosures:</b> NEMA 4 explosion-proof aluminum housing   |
| <b>Approximate Weight:</b> 8030 – 13 lbs (6 kg)  |
| <b>Approvals:</b> UL/CUL Class I, Division I, Groups C & D   |
| <b>Installation Information:</b> Provided with the monitor. Can also be accessed and downloaded via website. |

MADE IN



THE USA

Doc. No. GVM201808 – Rev. No. 1.0  
© Copyright OPW-ES 8/2018

2726 Henkle Dr. | Lebanon, OH | 45036

T: 1-800-547-9393 | F: 513-932-9845

[www.opw-es.com](http://www.opw-es.com)



**Engineered Systems**

PART OF OPW FLUID TRANSFER GROUP

A DDOVER COMPANY