## **Pipe**

## KPS™ 110 mm 4" Primary Piping

#### Conductive petrol pipes with permeation barrier

	Article Number	Description	Remark	Ø (mm)	Length (m)
ı	KP 110EC6	Pipe 110 mm, conductive	Pipe 110 mm, 5.8 m lengths. 20 units / package	110	116 m
	KP 110EC18	Pipe 110 mm, conductive	Pipe 110 mm, 18 m lengths. 1 unit / package	110	18 m
	KP 110EC30	Pipe 110 mm, conductive	Pipe 110 mm, 30 m coil.	110	30 m
1					





#### **Conductive connectors for pipe joints**

KP CC-110	Conductor 110 mm, conductive	110	24

Connectors used to bridge joints thereby maintaining conductivity throughout the pipe system. Patented design.

## **Welding Sockets**



Article Number	Description	Remark	Ø (mm)	Pack Size
KP 2-110	Welding socket 110 mm		110	10
KP 2-110R	Welding socket 110 mm, no pipe stop	Slides over the pipe	110	1

## **Bends, Elbows and Tees**

#### Conductive formed bends and elbows with permeation barrier




Article Number	Description	Remark	Ø (mm)	Pack Size
KP 3-110FC	Bend 90° 110 mm, conductive		110	1
KP 3-110FCL	Bend 90° 110 mm, conductive, long type	45 cm extra length	110	1
KP 4-110FC	Bend 45° 110 mm, conductive		110	1
Conductive well	dable alberre			

# KP 23-110C02 Elbow 90° 110 mm

Conductive toe with permeation barrier						
KP 24-110C02	Elbow 45° 110 mm, conductive	Weldable	110	6		
KP 23-110C02	Elbow 90° 110 mm, conductive	Weldable	110	5		

Equal tee



## **Entry Seals**



Article Number	Description	Remark	Ø (mm)	Pack Size
KP TM125/90	Entry seal, pipe 125/110/90 mm	Threaded, no bolts necessary. Use hole saw Ø 168 mm.	125/110/90	8
KP M160/90	Entry seal, pipe 160 to 90 mm	Use hole saw Ø 168 mm.	160/125/110/90	6
Blind entry se	eal			
KP TM125/90B	Blind entry seal, pipe 125/110/90 mm	Threaded, no bolts necessary. Use hole saw Ø 168 mm.	125/110/90	10

# **Transition Fittings**

Article Number	Description	Remark	Ø (mm)	Pack	
KP C17-110F	Transition fitting 110 mm, steel	4" BSPT female / Rc 4"	110	4	
KP C17-110FL	Transition fitting 50 cm stub, 110 mm, steel	4" BSPT female / Rc 4"	110		
(P C17-110/90F	Transition fitting 110/90 mm, reduced, steel	3" BSPT female / Rc 3"	110/90		
Male transitio	on fittings, conductive, plastic	to steel			
KP C17-110M	Transition fitting 110 mm, steel	4" BSPT male / R 4"	110		
KP C17-110ML	Transition fitting 50 cm stub, 110 mm, steel	4" BSPT male / R 4"	110		
KP C17-110/90M	Transition fitting 110/90 mm, reduced, steel	3" BSPT male / R 3"	110/90		
emale transition flange fittings, with spacer, conductive, plastic to steel					
KP C16-110F	Transition fitting 110 mm, steel	4" BSPT female / Rc 4"	110		
KP C16-110FL	Transition fitting 50 cm stub, 110 mm, steel	4" BSPT female / Rc 4"	110		
KP C16-110/90F	Transition fitting 110/90 mm, reduced, steel	3" BSPT female / Rc 3"	110/90		
Male transitio	on flange fittings, with spacer	, conductive, plastic to ste	el		
KP C16-110M	Transition fitting 110 mm, steel	4" BSPT male / R 4"	110		
KP C16-110ML	Transition fitting 50 cm stub, 110 mm, steel	4" BSPT male / R 4"	110		
KP C16-110/90M	Transition fitting 110/90 mm, reduced, steel	3" BSPT male / R 3"	110/90		
Conductive st	ub flanges, DIN flanges and g	askets for pipe terminati	on		
KP C20-110	Stub flange, DIN flange and gasket 110 mm, steel		110	;	
KP C20-110L	Stub flange, 50 cm stub, DIN flange and gasket 110 mm, steel		110		
KP W6-110	Separate threaded DIN flange 110 mm, steel	BSPT 4" female / Rc 4"	110		
C20-110/90	Stub flange, DIN flange and gasket 110/90 mm, steel		110		
Separate flange in stair	nless steel available upon request				
Compression	transition fittings, conductive	, plastic to steel			
KP C14-110/90M	Transition fitting, 110/90 mm, reduced, brass	3" BSPT male / R 3"	110		
Flange fitting	s				
KP F16-110MM	Flange fitting	4" BSPT male-male / R-R 4"			
KP F16-110MF	Flange fitting	4" BSPT male-female / R-Rc 4"			
KP F16-110FF	Flange fitting	4" BSPT female-female / Rc-Rc 4"			