

MIDLAND BOV'S INTERCHANGEABILITY CHART

TO MEET AAR LEVEL A PROTECTION

BOV VALVE REMOVED	MIDLAND PLUG STYLE		MIDLAND BALL STYLE	
	VALVE	SKID (IF REQUIRED)	VALVE	SKID
ACF LOW PROFILE (RATCHET STYLE)	A-549-JC A-566	(1)		
ACF A-585 PLUG	A-549	(1)		
ACF 2020 BALL	A-535	(1)		
ACF 2040 BALL	A-548	B-375 OR B-376	A-520	REQUIRED
ACF K2008	A-548	B-375 OR B-376	A-522	REQUIRED
ACF K2009	A-548	B-375 OR B-376	A-522	REQUIRED
HILLS-McCANNAN 4" EXTERNAL BALL	A-548	B-375 OR B-376	A-522	REQUIRED
JAMESBURY 4" 6RIB3 INTERNAL BALL	A-549-KB, A-565-KB	(1)		
JAMESBURY 4" AZFRC BALL	A-548	B-375 OR B-376	A-522	REQUIRED
JAMESBURY 4" SUZRC BALL	A-548	B-375 OR B-376	A-522	REQUIRED
JAMESBURY 4" AZFRL BALL	A-548	B-375 OR B-376	A-520	REQUIRED
JAMESBURY 4" SUZRL BALL	A-548	B-375 OR B-376	A-520	REQUIRED
JAMESBURY 4" 5REB3 BALL	A-535			
JAMESBURY 6" WSRR/WSRF WAFER-SPHARE BUTTERFLY	A-548	B-375 OR B-376	A-522	REQUIRED
TRINITY 4BFL-22HB-TT BALL	A-548	B-375 OR B-376	A-520-CS	REQUIRED
TRINITY 4BFL-36HB-TT BALL	A-548	B-375 OR B-376	A-520-MO	REQUIRED
TRINITY 4BFL-22HB-TTSJ BALL	A-548	B-375 OR B-376	A-520-CS-SJ1...SJ3	REQUIRED
TRINITY 4BFL-36HB-TTSJ BALL	A-548	B-375 OR B-376	A-520-MO-SJ1...SJ3	REQUIRED
TRINITY 4BF-22HB-TT BALL	A-548	B-375 OR B-376	A-522-CS	REQUIRED
TRINITY 4BF-36HB-TT BALL	A-548	B-375 OR B-376	A-522-MO	REQUIRED
TRINITY 4BF-22HB-TTSJ BALL	A-548	B-375 OR B-376	A-522-CS-SJ	REQUIRED
TRINITY 4BF-36HB-TTSJ BALL	A-548	B-375 OR B-376	A-522-MO-SJ	REQUIRED
UTC 3" INTERNAL BALL	A-549-KB, A-565-KB	(1)		
UTC 4" LOW PROFILE BALL	A-548	B-375 OR B-376	A-520	REQUIRED

NOTE: (1) NO SKID REQUIRED - EXISTING SADDLE PROTECTS THE VALVE TO LEVEL A.