

# Pressure Vacuum Vent

CIVACON's NV3000E high-flow pressure vacuum vent is designed for durability, safety and service performance.



NV3000E, Pressure Vacuum Vent

## Features and Benefits

- In accordance with EN14595
- **Pressure Die-Cast** aluminium design, stainless steel and acetal components for durability and longer life time
- **Automatic sealing** in case of a tanker rollover
- **Pressure Flow capacity** of 41 m<sup>3</sup>/h at 200 mbar
- **Vacuum Flow capacity** of 155 m<sup>3</sup>/h at 70 mbar
- **Lightweight** durable design (400 gram)
- **Removable filter** for easy serviceability
- **Viton GFLT** seals
- **Quick-Strip-In-place** design, no tools required
- **Suitable for** all Civacon 10" pressure activated fill-covers (PAF)
- **Double** dovetail grooves for poppet O-rings for a more secure and longer-lasting seal
- **1 1/4 BSPP** connection

## Related products

Art. number	Description
T400-series	Manhole cover assembly

## Spare parts

Article Nr.	Description
NV3000RK	Repair Kit NV3000E

*Spare part only supplied as complete kit*

### Contents Repair Kit NV3000RK

Item	Article Nr.	Description	Qty.
1	11745	Wave Spring	1
2	H71328	Vacuum Spring	2
3	H71329	Retaining Clip	2
4	H71330	Pressure Spring	2
5	9428	O-Ring 2-213 Viton A	1
6	11943	O-Ring 2-220 Viton A	2
7	6479	O-Ring 2-224 Buna-N	1
8	H71335	O-Ring 2-227 Viton A	1

## Ordering specifications

Art. number	Description
NV3000E	Pressure vacuum vent assembly (EN14595)

## Specifications

### NV3000E, PRESSURE VACUUM VENT

