

CC-3627-V03

H30035M, BALL, STN. STL, (57) REQ'D.

H-9431-RP THRUST RING, NYLON

H-9428-M SET SCREW, STEEL-CAD. PLT.

H-9429-M BEARING, P.T.F.E LINED

H-9432-M O-RING, Buna-N

H-9430-M BEARING, P.T.F.E LINED

C-20041-A BODY, CAST ALUM

H-9426-M WEAR RING, STEEL (2) REQ'D.

H-9427-F DUST SEAL, FELT

C-2984-AH RETAINER, ALUM.-HARDCOAT

C-2985-AH TAIL, ALLUM.-HARDCOAT-TEFLON IMPREG.

3 1/2" DIA

3" NPT, GAGE ONE THD LARGE

6 3/16" DIA

3" VICTUALIC CONNECTOR

3/8"-16 UNC  
1/2" DEEP

6 3/16"

TOLERANCE ON DIMENSIONS  
NOT OTHERWISE SPECIFIED  
DECIMAL ± .005"  
MACHINE FRACTIONAL ± 1/64"  
ROUGH CASTING ± 1/32"  
ANGLES ± 1/2°

DOVER - CINCINNATI, OHIO

Used on	Prod. No.

ASSEMBLY 3627-V0-3" SWIVEL			
<b>DOVER CORPORATION / OPW DIVISION</b> CINCINNATI, O., U. S. A.			
A	10483	05-04-90	DF
REL.	10109	11-30-88	TJJ
Letter	Ex. No.	Date	Drawn
CHANGE			
DRAWN BY: RWILLIGER		SCALE: NONE	
TRACED BY:		DATE: 1/23/85	
CHECKED BY: [Signature]		APPROVED: [Signature]	
DRAWING No. CC3627V03			