

Features & Benefits:

- ◆ Watertight – structure will not deform under water pressure
- ◆ Tank Sump bury depths 40" to 60". For depths greater than 60", see extensions below.
- ◆ Vacuum testable – during and after installation
- ◆ Available for both new and retrofit applications



FIBRELITE 
PART OF OPW A DÜRRER COMPANY

Fibrelite Tank Sumps

OPW Fibrelite tank sumps function as a liquid-tight isolation container providing secondary containment for tank fittings valves, pumps and Flexworks or Fiberglass pipe fittings.


They also provide surface access to the tank itself, as well as a clean, dry environment for future service and maintenance. The height - adjustable risers to accommodate different tank bury depths.

Ordering Specifications - Complete Tank Sump Kits

Part #	Dia.	Overall Height	Base	Reducer Opening	Cover	Weight (lbs)
S8SB-390WT-KIT	45"	39"	Solid	33"	33"	138
S8SBD-390WT-KIT	45"	48"	Solid	33"	33"	146
S8CR-390WT-KIT	45"	48"	Collar Ring	33"	33"	116
S8CRD-390WT-KIT	45"	63"	Collar Ring	33"	33"	93
S14CR-390WT-KIT	52"	48"	Collar Ring	33"	33"	138
S15CR-390WT-KIT	57"	51"	Collar Ring	33"	33"	165

Kit's include Base, Reducer and Cover.
Resin Kit must be ordered separately.

Ordering Specifications - Sump Base



Part #	Application	Dia.	Height	Base	Weight (lbs)
S45	18" Dia. X 18" Deep FRP Solid Base Sump	18"	18"	Solid	33
S8SB	45" Dia. X 24" Deep FRP Sump W/ Solid Structural Base	45"	24"	Solid	90
S8SBD	45" Dia. X 33" Deep FRP Sump W/Solid Structural Base	45"	33"	Solid	98
S8CR	45" Dia. X 33" Deep FRP Sump W/ 42" Collar Ring Attachment	45"	33"	Collar Ring	68
S8CRD	45" Dia. X 45" Deep FRP Sump W/ 42" Collar Ring Attachment	45"	45"	Collar Ring	45
S14CR	52" Dia. X 33" Deep FRP Sump W/48" Collar Ring Attachment	52"	33"	Collar Ring	75
S15CR	57" Dia. X 36" Deep FRP Sump W/54" Collar Ring Attachment	57"	36"	Collar Ring	100

Tank SUMP BASE, TOP-HAT, COVER and RESIN KIT must be ordered separately.

Ordering Specifications - Optional Extensions for Deep Bury



Part #	Application	Dia.	Reducer Opening	Weight (lbs)
S8-EX12	12" Deep Yellow FRP Extension For S8 Sump	45"	12"	18
S14-EX12	12" Deep Yellow FRP Extension For S14 Sump	52"	12"	21
S15-EX12	12" Deep Yellow FRP Extension For S15 Sump	57"	12"	23

Ordering Specifications - Top-Hat



Part #	Application	Dia.	Reducer Opening	Weight (lbs)
S42-3100-TH	42" Dia. Round Sump - 37" Dia. Reducer Opening Other FRP Sumps	42"	37"	36
S8-390-TH	S8 Sump system includes retaining ring	45"	33"	35
S8-3100-TH	S8 Sump system includes retaining ring	45"	37"	37
S14-390-TH	S14 Sump system includes retaining ring	52"	33"	40
S14-3100-TH	S14 Sump system includes retaining ring	52"	37"	49
S15-390-TH	S15 Sump system includes retaining ring	57"	33"	50
S15-3100-TH	S15 Sump system includes retaining ring	57"	37"	52

Ordering Specifications - Turbine Sump Watertight Cover Lids



Part #	Application	Dia.	Weight (lbs)
WT-31	31" Dia. Watertight, Structural Spill Platform	31"	11
WT-33	33" Dia. Watertight, Structural Spill Platform	33"	13
WT-37	37" Dia. Watertight, Structural Spill Platform	37"	17

Ordering Specifications - Sump Accessories

Part #	Application
SL-1100	Urethane Sealant
S-CS-SEALANT	2 Part Self Leveling Sealant - Used to Seal Gap Between the Top-Hat and Skirt
S-CR-FGK	Kit for Bonding Collar Ring to Tank Collar - Includes Resin, Catalyst and Glass Tape.
RK-5000	Epoxy Resin Kit Bonding Collar Ring Sump to Fiberglass Tank Collar
PLEX-TUBE	1 Tube Of Plexus Adhesive
PlexisApplicator	Single Barrel Manual Applicator

Contact OPW for Tank Fittings and Manway Adaptors - 1-800-422-2525

Ordering Specifications - Sump Accessories

Part #	Application
WSP-WTS-OPC	6" Nitrile Observation Port Cap for WSP
WTS-CAP-14	14" Nitrile Container Port Cap for WSP
WS-RING-31	31" Stainless Steel Retaining Ring for Top-Hat
WS-RING-33	33" Stainless Steel Retaining Ring for Top-Hat
WS-RING-37	37" Stainless Steel Retaining Ring for Top-Hat
S-TH-RISER-31	10" Deep Top-Hat Riser for All 31" Dia. Opening
S-TH-RISER-33	10" Deep Top-Hat Riser for All 33" Dia. Opening
S-TH-RISER-37	10" Deep Top-Hat Riser for All 37" Dia. Opening



New Latched Fiberglass Tank Sump Lids

Our new specially designed latched Fiberglass Tank Sump Lid is now available on our Fiberglass Sump Models. Our new lid can also be ordered as a replacement Lid for our Polyethylene Sumps.

This lid is available to replace the "Mechanically Fastened" lids with knobs on retrofit applications.

Features & Benefits:

- ◆ Six latch and cover design to ensure even sealing.
- ◆ Holes in the lid to allow installation on 33" Fiberglass or Polyethylene Tank Sumps.
- ◆ Lid strength is three times stronger than our previous lid.
- ◆ Retrofitable to existing OPW Polyethylene and Fiberglass Tank Sumps that have the Mechanically Fastened Lid.

Ordering Specifications - New Latched Fiberglass Tank Sump Lids

Part #	Description
CLC-33	Latched Fiberglass Tank Sump Lid
LRK-CLC	Latch Replacement Kit for the CLC-33