

FibreTite Tank Sump

From the engineering labs of Flexworks and Fibrelite, OPW has made the best even better. Meet the newest member of the FibreTite Family of sumps, the most watertight sumps on the market today. Designed to meet all the new 2018 EPA UST regulations.

Materials:

Sump: Resin Transfer Molding (RTM) technology



FibreTITE
TANK SUMP

Features & Benefits:

- ◆ The only sump manufactured using superior Resin Transfer Molding (RTM) technology. The RTM process utilizes a two-sided mold to ensure consistent wall thickness and exceptionally smooth wall surfaces inside and out for an ultra-tight entry fitting sealing surface
- ◆ Two-piece top-hat design allows for tailored height adjustments
- ◆ Inverted U-Channel allows for equal resin distribution, creating a superior bond between the base and the top hat to eliminate water intrusion
- ◆ Stainless-steel ring and watertight sealing gasket provide the proven seal-ability of our world-renowned Fibrelite sumps
- ◆ Available with and without bottom for collar or flange mounting
- ◆ Ergonomic "L-Handle" provides ease of use and a visual indicator that the handle is in the locked position and the watertight lid is secure

Ordering Specifications - Tank Sump Systems

	New Name	Max Sump Height (A)	Min Sump Height (A)	Sump Base Diameter (B)	Sump Mount Design	Sump Lid Diameter (C)	Minimum Diameter Opening (D)	Additional RK-5000 Resin Kits Needed for Top Hat Attachment (Sold Separately)	Additional RK-5000 Resin Kits Needed for Collar Ring Attachment (Sold Separately)
42"	FTSM-4233CR	46"	33.5"	42"	Collar Ring Mount	34.8"	29"	1	1
	FTSM-4233SB	46"	33.5"	42"	Solid Bottom	34.8"	29"	1	-
	FTSD-4233CR	53"	40.5"	42"	Collar Ring Mount	34.8"	29"	1	1
	FTSD-4233SB	53"	40.5"	42"	Solid Bottom	34.8"	29"	1	-
	FTSM-4237CR	46"	33.5"	42"	Collar Ring Mount	39.5"	34.6"	1	1
	FTSM-4237SB	46"	33.5"	42"	Solid Bottom	39.5"	34.6"	1	-
	FTSD-4237CR	53"	40.5"	42"	Collar Ring Mount	39.5"	34.6"	1	1
	FTSD-4237SB	53"	40.5"	42"	Solid Bottom	39.5"	34.6"	1	-
48"	FTSM-4837CR	46"	33.5"	48"	Collar Ring Mount	39.5"	34.6"	1.5	1
	FTSD-4837CR	53"	40.5"	48"	Collar Ring Mount	39.5"	34.6"	1.5	1
	FTSM-4837SB	46"	33.5"	48"	Solid Bottom	39.5"	34.6"	1.5	-
	FTSD-4837SB	53"	40.5"	48"	Solid Bottom	39.5"	34.6"	1.5	-

Replacement Parts/Accessories

Part #	Description	Part #	Description
FTSMBASE-42CR	42" Medium Bury Collar Mount	WT-33SL	33" Fibretite Sump Lid
FTSMBASE-42SB	42" Medium Bury Solid Bottom	WT-37SL	37" Fibretite Sump Lid
FTSMBASE-48SB	48" Medium Bury Solid Bottom	FCS42-EX12	42" Diameter Sump 12" Extension (1 RK-5000 kit needed for attachment sold separately)
FTSMBASE-48CR	48" Medium Bury Collar Mount	FCS48-EX12	48" Diameter Sump 12" Extension (1.5 RK-5000 kit needed for attachment sold separately)
FTSDBASE-42CR	42" Deep Bury Medium Bury Collar	RK-5000	1 Quart Epoxy Resin Kit
FTSDBASE-42SB	42" Deep Bury Solid Bottom	S-CR-FGK	Optional Glassing Kit for Collar Ring Attachment
FTSDBASE-42SB	48" Medium Bury Solid Bottom	WT-LID-GASKET	Gasket Seal and Epoxy for WT, WSP, WTS Lids
FTSDBASE-48CR	48" Deep Bury Collar Mount	WT-LID-GASKET-TOOL	Installation tool for WT-LID-GASKET
FTS-4233TH	Top Hat for 42" Base Sump (33" opening)		
FTS-4237TH	Top Hat for 42" Base Sump (37" opening)		
FTS-4837TH	Top Hat for 48" Base Sump (37" opening)		

