



LPG Accessories OAS400 3/4" Nozzle Reconnectable Breakaway

The OPW OAS400 3/4" Breakaway with Anchor Strap is designed for in-line use with any LPG fueling system. Valve inlet has 3/4" BSPP threads. Safely shuts off fuel flow in the event of a vehicle driveaway.

Materials

Body: Steel (brass optional)
Internal Components: Brass and steel
Seals: Specially formulated polymers and elastomers specific to LPG applications.



OAS400

Features

- ◆ **Durable Construction** - heavy-duty brass, aluminum and steel construction provides excellent corrosion resistance in the harsh fueling environment.
- ◆ **Added Safety** - anchor strap allows for installation anywhere and added assurance.
- ◆ **Patented Front Compression Collar Provides Ease of Use** - breakaway can be reconnected without tools by simply turning the front ring to compress the locking sleeve. Reinsert the breakaway portion of the safety valve and then unscrew front ring to allow locking sleeve to return to its original position.

- ◆ **Individually Leak Tested and Inspected**

Specifications:

MAWP: 350 psi (24 bar)
 Separation Force: 45-112 lbs. (200-500N)
 Temperature Range: -40° F to 185° F
 (-40° C to 85° C)

Ordering Specifications

Product #	Inlet Thread Size	Material	Service Pressure		Weight
OAS400	3/4" BSPP Female	Brass	350 psi	24 bar	2.314 lbs. (1.05 kg)