

- Watertight pipe and conduit entries
- Maximum flexibility to accommodate pipe and ground movement
- Added flexibility providing quick and easy installation
- Provides clean, dry environment inside tank and dispenser sumps and accommodates various site installations
- Allows for easy field adjustments
- Can be repaired if damaged
- Internal and external clamps provide dual positive seal-off points
- Third-party tested and approved by UL/ULc
- Available heat-trace entry fittings with grommet

Round-Kit Guide

Original Part #	Plus	Kit for Round Sumps
HEF-4075		
HEF-4010		
HEF-4015(A/G)		
HEF-4020(A/G)		
HEF-4175	+	ROUNDKIT-14
HEF-0150		
HEF-0200		
REF-0150		
REF-0200		
HEF-6030		DOUNDKIT 46
HEF-0300	+	ROUNDKIT-16
REF-4015		ROUNDKIT-24
REF-4020	+	KOUNDKII-24

Hybrid Entry Fittings

FlexWorks Hybrid Entry Fittings are designed to seal the sump penetration. These entry fittings bring the best of both worlds from the robust and popular REF and legacy DEB lines of products. The outer buried half features a hard-shell exterior to weather the elements and abuse of the underground environment, the same as you find on an REF. The inner accessible half provides the flexibility of the DEB. The sealing redundancy throughout the fitting provides maximum containment and unmatched protection from water intrusion.



Ordering Specifications -Hybrid Entry Boot & Fitting

Entry Fitting with **Heat Tracing**

Model # Application		Hole Saw	
		in.	cm
HEF-0751	1/2", 3/4", and 1" Conduit Hybrid Entry Fitting	21/2"	6.35
HEF-4010	4" to 1.0" Hybrid Entry Fitting for 4" Flexworks Access Pipe to 1.0" DW Flexworks Pipe	4"	10.16
HEF-4075	4" to 0.75" Hybrid Entry Fitting for 4" Flexworks Access Pipe to 0.75" DW Flexworks Pipe	4"	10.16
HEF-4015*	4" to 1.5" Hybrid Entry Fitting for 4" Flexworks Access Pipe to 1.5" DW Flexworks Pipe	4"	10.16
HEF-4015A	Hybrid Entry Fitting, 1.5" with Air Stem	4"	10.16
HEF-4015G	Hybrid Entry Fitting, 1.5" with Grommet for Heat Tracing	4"	10.16
HEF-4020*	4" to 2.0" Hybrid Entry Fitting for 4" Flexworks Access Pipe to 2.0" DW Flexworks Pipe	4"	10.16
HEF-4020A	Hybrid Entry Fitting, 2.0" with Air Stem	4"	10.16
HEF-4020G	Hybrid Entry Fitting, 2.0" with Grommet for Heat Tracing	4"	10.16
HEF-6030*	6" to 3.0" Hybrid Entry Fitting for 6" Flexworks Access Pipe to 3.0" DW Flexworks Pipe	53/4"	14.61
HEF-4175	4" to 0.75" and 1.0" Hybrid Entry Fitting for Fuel-Oil applications	4"	10.16

^{*} For round-sump compatibility, add the correct ROUNDKIT for your application.

