

Access Pipe

A 4" or 6" diameter corrugated flexible conduit is used to provide access to and permit the future replacement of the flex piping if desired. This corrugated pipe is strong enough to withstand H-20 loading requirements when properly buried and thick enough to minimize damage from shipping and jobsite handling. Access pipe can accommodate the 3/4", 1", 1-1/2", 2" and 3" FlexWorks supply pipe.

Features & Benefits:

- ◆ Crush and puncture-resistant
- ◆ Semi-smooth liner facilitates ease of installation
- ◆ Saves you time and money
- ◆ No buried joints



Ordering Specifications - FlexWorks Access Pipe

Part #	Application	Minimum Bend Radius		Packaging		Dimensions				Box Size		Weight	
		in.	mm			I.D.		O.D.		in.		lbs.	kg
AXP40-100	4" Dual Layer Access Pipe	18"	457	Box	100 ft.	4	102	4.760	121.0	42x42x32		115	52
AXP40-250	4" Dual Layer Access Pipe	18"	457	Box	250 ft.	4	102	4.760	121.0	60x60x32		218	99
AXP60-500	6" Access Pipe	36"	914	Box	500 ft.	6	152	7.100	180.0	96x60x32		485	220
AXP60-100	6" Access Pipe	36"	914	Box	100 ft.	6	152	7.100	180.0	48x48x32		125	57
AXP40-Connect	4" Connection Boot											1	

Access Pipe Installation Instructions Sheet Order Number: **API-0001**