


OPW 623V Pressure Vacuum Vent

Pressure Vacuum Vents are installed on the top of vent pipes from underground or above ground fuel storage tanks. The vent cap and internal wire screen are designed to protect the tank vent lines against intrusion and blockage from water, debris or insects. A normally closed poppet in the valve opens at a predetermined pressure or vacuum setting to allow the tank to vent.



Conversion Table

Measurement Units	=	Oz.	PSI	In H ₂ O (WC)	In Hg (Merc)	Bar
Bar	x	236.0	14.5	401.4	29.53	
In. Hg (Mercury)	x	7.843	0.49	13.6		0.034
In H ₂ O (WC)	x	0.578	0.04		0.074	0.002
PSI	x	16.00		27.68	2.04	0.069
Oz.	x		0.063	1.73	0.128	0.004

Materials

- Top/Body:** Polypropylene
- Base:** Anodized aluminum
- Poppet:** Anodized aluminum
- Screen:** Stainless steel mesh
- Gasket:** Closed cell foam

623V

Vent Must Be Mounted Vertically



Features

- ◆ Pressure/Vacuum Setting – 2.5" to 6" water column pressure settings and -6" to -10" water column vacuum settings are factory preset and tested.
- ◆ Reliable Service – cycle tested to the equivalent of 80 years of service in the most severe environment without leakage problems.
- ◆ Corrosion-Resistant Construction – a Duratuff® composite body ensures a long service life.
- ◆ Easy Installation – the 623V is available in 2" and 3" threaded versions.
- ◆ Complies with NFPA 30 Requirements – for venting gasoline vapors upward.
- ◆ Manifold Vent Pipes – vent pipes may be manifolded to produce a single Pressure Vacuum Vent line. The 623V exceeds California's requirements of a maximum vapor leak rate of 0.17 SCFH at 2.00 inches H₂O.
- ◆ High Maximum Flow Rate – 6450 SCFH at 2 psi (0.1 bar) pressure drop.
- ◆ Leak Rate – multiple pressure vacuum vents may be installed on a single site. The 623V exceeds California standards with a leak rate of 0.05 SCFH or less at 2.00 inches H₂O.
- ◆ Maintenance – no tools required. A removable snap fit top allows for easy maintenance (recommended yearly).
- ◆ 100-Mesh Stainless Steel Wire Screens – helps prevent debris and insects from entering the tank vent lines. An added screen installed at the base prevents debris from intruding from the vent stack.
- ◆ Adaptor Bushing – removable hex threaded bushing designed for easy installation on NPT threaded risers. Allows easy access to lower screen.
- ◆ ATEX Approved – for flame arrestor applications

623V Instruction Sheet Order Number: H14898PA

Ordering Specifications

Product #	Description	Identification Label Color	lb.	kg
623V-2203	2.5" to 6" WC Pres., -6" to -10" WC Vac. 2" Thread-On	Yellow	1.55	.70
623V-3203	2.5" to 6" WC Pres., -6" to -10" WC Vac. 3" Thread-On	Yellow	2.20	1.00

Replacement Parts

Part Number	Description
C05086M	Lower Screen
H14895M	Upper Screen
C05089	2" Threaded Base Adaptor
C05122	3" Threaded Base Adaptor

Listings and Certifications



OPW 623V & 523V



ATEX Approved

Patent No. WO2004/036096AZ