

### Options and Replacement Parts

| Part #    | Description                                     | Counterweight Length |      | Weight |      |
|-----------|---|----------------------|------|--------|------|
|           |   | in.                  | cm   | lbs.   | kg   |
| H15262    | Counterweight for 4000/AGNV Models              | 27"                  | 68.5 | 24     | 10.8 |
| H15263    | Counterweight for 5000 Model                    | 31"                  | 78.7 | 27     | 12.2 |
| H15260    | Counterweight for 6000 Model                    | 20"                  | 50.8 | 17     | 7.7  |
| H15261    | Counterweight for 7000, 8000, 9000, AGBR Models | 25"                  | 63.5 | 22     | 9.9  |
| H15265M   | Sliding Bracket, Dispenser Mount                |                      |      |        |      |
| P100-HL   | Highline Mounting Bracket                       |                      |      |        |      |
| C05235M   | Replacement Tube, 2"x 2"x 75" (191 cm)          |                      |      |        |      |
| C05236M   | Replacement Tube, 2"x 2"x 88" (224 cm)          |                      |      |        |      |
| C05237M   | Replacement Tube, 2"x 2"x 120" (305 cm)         |                      |      |        |      |
| D02671M   | Replacement Housing, Plastic                    |                      |      |        |      |
| H15266    | Top and Pulley Assembly                         |                      |      |        |      |
| H15264    | Replacement Cable                               |                      |      |        |      |
| C05239M   | Retractor Foot                                  |                      |      |        |      |
| P100-3F   | Freestanding Retractor Base                     |                      |      |        |      |
| P100SPOOL | Replacement Cable Spool, 1000'                  |                      |      |        |      |
| P100-AL   | Aluminum Housing                                |                      |      |        |      |
| H15266    | Plastic Top & Pulley Assembly                   |                      |      |        |      |

## POMECO 100 COUNTERWEIGHT T-TOP RETRACTORS


The T-Top Air/Water model separates the hoses allowing one hose to be used while the other remains safely out of the way.



### Ordering Specifications

#### Hose Clamps

| Model Number | Hose Size/Type†                        |
|--------------|--|
| PB-1396      | Standard 1½" O.D. Hose (1" I.D.)       |
| PB-1394      | Standard 1½" O.D. Hose (¾" I.D.)       |
| PB-1375      | Standard 1½" O.D. Hose (⅝" or ¾" I.D.) |
| PB-1373      | Standard 1" O.D. Hose (⅝" I.D.)        |
| PB-1344      | Balanced Coaxial, Goodyear Premier     |
| PB-1340      | Balanced Coaxial, Dayco Petroflex      |



Hose Clamp

### Ordering Specifications

#### Air/Water Hose Applications

| Model Number | Description  | S Hose Length |        | Height |     | Weight |      |
|--------------|--|---------------|--------|--------|-----|--------|------|
|              |  | ft.           | meters | in.    | cm  | lbs.   | kg   |
| 6100-DAWO    | Air/Water Hose Retractor (complete with dual hose) | 18.5'         | 5.6    | 124"   | 315 | 26     | 11.8 |
| 6100-DAOO    | Air Hose Retractor (complete with air hose)        | 18.5'         | 5.6    | 124"   | 315 | 23     | 10.4 |
| 6100-DANC    | Air Hose Retractor (with hose clamp only)          |               |        | 124"   | 315 | 20     | 9.1  |
| 6100-DANH    | Air Hose Retractor (no hose or clamp)              |               |        | 124"   | 315 | 20     | 9.1  |

### Important

FlexWorks by OPW, Inc., VAPORSAVER™ and all other OPW products must be used in compliance with all applicable federal, state, provincial and local laws, rules and regulations. Product selection must be based on physical specifications and limitations, compatibility with the environment and material to be handled. All illustrations and specifications in this literature are based on the latest production information available at the time of publication. Prices, materials and specifications are subject to change at any time, and models may be discontinued at any time, in either case, without notice or obligation. OPW warrants solely to its customer that the following products sold by OPW will be free from defects in materials and workmanship under normal use and conditions for the periods indicated.