

Materials

- Body:** Die-cast zinc
- Protective Sleeves:** Impact modified nylon
- Main Seals:** Viton®
- Main Spring:** Stainless steel
- Guide and Poppets:** Acetal



66CL-0250

Features

- ◆ UL listed for use in gasoline, diesel and up to 10% ethanol blends. Specific listings available at www.opwglobal.com.
- ◆ **Valve Poppets** – close on both ends of breakaway to limit fuel spillage.
- ◆ **Sleek, Attractive Appearance** – to enhance station image.
- ◆ **Easy, 2-Hand, “Push-n-Twist” Reconnect** – to help put dispenser back in service quickly. Always inspect the entire dispensing system for damage or leakage after a drive-away. Replace damaged parts.
- ◆ **Rugged, Durable Construction** – Duratuff® outer sleeve to protect coupling and sealing parts from damage for long, trouble-free service life.
- ◆ **Designed to breakaway at a maximum of 250 pounds of axial pull force** – OPW Coaxial Breakaways help minimize nuisance breaks.

Design working pressure

- ◆ 50 psi (3.45 bar) maximum pressure.

Ordering Specifications

Product #	Description
66CL-0250	In-line coaxial breakaway

66CL Series Instruction Sheet Order Number: H11487PA

Listings and Certifications



CARB
California Air Resources Board

OPW 66CL Coaxial Breakaways

The OPW 66CL Reconnectable Breakaway is designed for all in-line balance applications.

All Versions of Balance Breakaways – Approved On All Balance Systems

	66CL	66CSU-5200	66CLP-5100
Reconnectable	●		●
Single Use		●	
Vapor Poppet			●

