



BY OPW FUELING CONTAINMENT SYSTEMS

FlexWorks Double Wall Flexible Piping

In keeping with OPW's beliefs in environmental safety, FlexWorks smooth bore flexible double wall piping by OPW Fueling Containment Systems has a secondary Closed System Rating of 50 PSI necessary for use in California and other areas requiring **Closed System** approvals.

The Flexible Piping SOLUTION for CALIFORNIA and other areas requiring Closed System approval

Part #	Application
CO75-250	Double-Wall Primary Pipe, 3/4", Box 250 ft.
CO75-1000	Double-Wall Primary Pipe, 3/4", Reel 1,000 ft
C10-250	Double-Wall Primary Pipe, 1, Box 250 ft.
C10-1000	Double-Wall Primary Pipe, 1", Reel 1,000 ft
PGFC-2150B	Double-Wall Primary Pipe, 1.5", Box 250 ft
PGFC-2150R	Double-Wall Primary Pipe, 1.5", Reel 1,000 ft.

UL/cUL



OPW-FCS 1.0" UNDERGROUND USE ONLY
100 psi(863 kPa) PRI / 50 psi (345 kPa) SEC MAX WP

OPW Fueling Containment Systems

3250 US 70 Business West
Smithfield, N.C., 27577-0330

Customer Service: 1-800-422-2525

Customer Service Fax: 1-800-421-3297

Technical Service: 919-934-2786

www.opwfcs.com



Publication: FCA-0001
Issue Date: 02/01/08

Notice: OPW-FCS products must be used in compliance with applicable federal, state, provincial and local laws and regulations. Product selection should be based on physical specifications and limitations and compatibility with the environment and material to be handled. OPW-FCS makes no warranty of fitness for a particular use. All illustrations and specifications in this literature are based on the latest production information available at the time of publication. Prices, materials and specifications are subject to change at any time, and models may be discontinued at any time, in either case, without notice or obligation. For complete OPW-FCS warranty information, visit our web site at www.opwfcs.com.