

Specifications

Internal Rechargeable
Battery Powered
Height: 6"
Width: 12"
Depth: 8"
Weight: 15.75 lbs. (5.78 kg)



Features

- ◆ **Portable** – no external power nor pressure required to operate the unit.
- ◆ **Operation** – no difficult to read flow meters to read, nor knobs or switches to adjust. Simple one push button operation.
- ◆ **Print Out** – all values for each test are printed out along with specifications, a place to give the station name, and personnel testing. Each test is date stamped for your convenience.
- ◆ **Calibration** – tester is required to be calibrated every 6-months. Calibration is to be performed at OPW. A special cap is included to verify system integrity on a day-to-day basis.
- ◆ **Power** – 12V automotive plug-in power cord and 110 AC Power cord included for recharging.
- ◆ **Testing Standard** – unit will test both EVR and pre-EVR approved P/V Vent Valves.

Ordering Specifications:

Product #	Description	lb.	kg
X23-2000	Automatic P/V Valve Tester	15.75	5.78
202506	523 Test Adaptor		
X23-2000-CAL	Calibration		

OPW X23-2000 Automatic P/V Vent Valve Tester

Test Equipment for all CARB EVR and pre-EVR Pressure Vacuum Vents



Valves Testable:

Applicable with both CARB EVR and pre-EVR pressure vacuum vants. Consult your operator's manual for item specifics