

OPW 19DEF Series Industrial Automatic Nozzle

When you're responsible for ensuring the safe, reliable and affordable dispensing of Diesel Exhaust Fluid (DEF) for on-road, off-road, commercial and industrial heavy-duty trucks, farming or other diesel powered vehicles, you rely on the most trusted name in dispensing nozzles — OPW.

The NEW OPW 19DEF Series Industrial Automatic Nozzle is specifically designed for your commercial and industrial fleet operations, offering unmatched reliability with the features you want.

OPW 19DEF Series Swivels

Reconnectable Swivel Breakaway



- Designed to connect to the inlet of the nozzle. -No whip hose needed
- The industries best swiveling ability
- Breakaway is reconnectable with built in swivel / Retaining jaws and seals are replaceable
- Breakaway will separate at no more than 350 pounds of force. (axial or angular)

Hose Swivel



- Hose swivel designed for 3/4" DEF hose (Clamps not included)
- The industries best swiveling ability



 The industries best swiveling ability

Design Working Pressure

 50 PSI (3.45 bar) maximum pressure

NOTE: The OPW 19DEF Equipment is for commercial fleet applications only and are not UL Listed for gasoline dispensing facilities.

Materials

Packing & Disc: Fluorocarbon Lever & Lever Guard: Duratuff®

Spout: Stainless Steel

O.D. 19mm (0.75 in) per ISO 22241

Specifications

Inlet Size: 3/4" NPT or 3/4" BSPP Weight: 2.73 lbs. each, 43.1 lbs./case

> of 15, 1.25 kg each, 19.9 kg/case of 15



Features - Benefits

- Stainless Steel Spout provides optimum DEF purity and prevents corrosion
- Lowest Overall Cost of Ownership reliable, long lasting design based on proven OPW quality platform and industry standard-setting technology
- Ease of Use sleek, lightweight design with patented Accu-Stop® Flow Control Technology and convenient one-finger hold-open clip to set flow rate
- User Comfort attractive 2-Piece NEWGARD™ Hand Insulator is the most comfortable nozzle in the industry in hot or cold weather
- Vehicle Protection our Duratuff® lever guard not only provides for rugged durability when dropped but also won't scratch your fleet vehicle
- Meets ISO 22241 Requirements all materials of construction are 100% 3rd party tested and approved for DEF compatibility

Product #	Description
Nozzles	
19DEF-0500SS	Nozzle - 19mm spout; 3/4" Female NPT inlet connection, blue hand warmer.
19DEF-050LSS	Nozzle - 19mm spout; 3/4" Female BSPP inlet connection, blue hand warmer
19DEFM-0500SS	Nozzle, 19DEFM, 3/4" NPT, Blue 2 PcHI 2 Pos Rack
19DEFM-050LSS	Nozzle, 19DEFM, 3/4" BSPP, Blue 2 PcHI 2 Pos Rack
Swivel Breakaway	
19DB-0075	Breakaway, DEF, 3/4" NPT
19DB-0075L	Breakaway, DEF, 3/4" BSPP
Hose Swivel	
19DHS-0075	Hose Swivel, DEF, 3/4" NPT
19DHS-0075L	Hose Swivel, DEF, 3/4" BSPP
Swivel	
19DS-0075	Swivel, DEF, 3/4" NPT
19DS-0075L	Swivel, DEF, 3/4" BSPP
Hose Adaptors	
19DM-0100	3/4" MNPT to 1" MNPT - Connecting nozzle to 1" NPT Female hose
19DF-0100	3/4" MNPT to 1" FNPT - Connecting nozzle to 1" NPT Male hose
19DML-0100	3/4" MBSPP to 1" MBSPP - Connecting nozzle to 1" BSPP Female hose
19DFL-0100	3/4" MBSPP to 1" FBSPP - Connecting nozzle to 1" BSPP Male hose
19DML-0075	3/4" MBSPP to 3/4" MBSPP - Connecting nozzle to 3/4" BSPP Female hose