Meets ISO 22241 **Materials** Compatibility Testing for DEF Contamination 21Gu-0500 Body: Special resin coated aluminum Lever & Lever Guard: Duratuff® Seals: Viton® Inlet Size: M34 (adaptor required for each nozzle) Weight: 2.41 lbs. each, 36 lbs./case of 15 1.1 kg each, 16.5 kg/case of 15 **Mis-Filling Prevention** Device (MFPD)

Features - Benefits

- Automatic Shutoff Feature shuts off nozzle when the tank is full
- Mis-filling prevention device eliminates the risk of accidental DEF filling or environmental contamination.
- Spout with magnetic interface prevents mis-filling mishaps.
- Durable streamlined nozzle design for easy, comfortable nozzle handling makes it easy to differentiate DEF products.
- Total end-to-end affordable solution is a convenient and complete system from the Industry Leader.

- Comes with Integral Contaminant-Prevention Filter; this replaceable, stainless steel, 40-mesh filter provides an added level of protection against DEF contaminants.
- Outfitted in that familiar and unmistakable "DEF Blue" with slogan badge for instant product identification.



21GU-FLTR


Maximum pressure and flow rate

- 40 psi (2.75 bar) maximum pressure.
- ◆ 10 gpm (37.8 lpm) maximum flow rate

OPW 21Gu™ DEF Nozzle

The Industry's Most **Comprehensive DEF-Filling** Solution

- End-to-end dispensing hardware solution for reliable, efficient **DEF-filling**
- Industry standard DEF-filling solution in Europe
- Unique Mis-Filling Prevention Device (MFPD) provides unparalleled filling assurance and peace of mind
- Affordable mis-filling prevention insurance designed to protect your investment against potential mis-filling mishaps



Are You Protected?

A fixed magnetic field within the Mis-Filling Prevention Device actuates a magnetic interface in the spout of the 21Gu nozzle to allow the flow of DEF. Without the Mis-Filling Prevention Device, the DEF nozzle will not flow. Put the nozzle in the wrong tank - say, your diesel tank - no problem, the nozzle will not flow. No other DEF-filling nozzle has this DEF mis-filling protection capability.

MIS-FILLING PREVENTION

WITH the OPW 21Gu nozzle and Mis-Filling Prevention Device (MFPD), your investment is safe.






Nozzle Magnetic Interface is Not Actuated and DEF **Cannot Contaminate** Your Diesel Fuel Tank



Other DEF Nozzle

WITHOUT the OPW 21Gu nozzle and Mis-Filling Prevention Device (MFPD), your investment is at risk.





There is Nothina to Stop the Nozzle from Contaminating Your Diesel **Fuel Tank** No


Listings and Certifications

ISO 22241 Compliant



Nozzle Ordering Specifications

Product #	Description
21GU-0400	Wayne® / Bennett® / Gasboy® (Model 9862XX-ZWW) Nozzle designed for use WITHOUT Mis-Filling Prevention Device
21GU-040G	Gilbarco® / Gasboy® (Model 9862KX-Z) Nozzle designed for use WITHOUT Mis-Filling Prevention Device
21GU-0500	Wayne® / Bennett® / Gasboy® (Model 9862XX-ZWW) Nozzle designed for use WITH Mis-Filling Prevention Device
21GU-050G	Gilbarco® / Gasboy® (Model 9862KX-Z) Nozzle designed for use WITH Mis-Filling Prevention Device





Bennett®, Separation by Design®, Wayne® Guard (Standard) and Gasboy®



Gilbarco® Guard

Replacement Parts

Product #	Description
206466	21GU-0500 & 050G Blue Hand Insulator
205077	21GU-0400 & 040G Black Hand Insulator
21GU-SPOUT	DEF Replacement Spout designed for use WITH Mis-Filling Prevention Device
21GU-SPOUT-N	DEF Replacement Spout WITHOUT Mis-Filling Prevention Device
204133	DEF Replacement Slogan Badge
21GU-FLTR	Strainer and Spacer Washer

CHOOSE YOUR NOZZLE OUTLET STYLE

21GU-SFH Stainless Steel Fixed Hose Fitting

21GU-SSS Stainless Steel Swivel

21GU-SSR

Stainless Steel Swivel / Reconnectable Breakaway



Features

- SST construction and compatible with ISO 22241 Standard
- Converts nozzle from M34 threads to 1" BSPP



- SST construction and compatible with
- ISO 22241 Standard
- Converts nozzle from M34 threads to 1" BSPP
- Long lasting single plane swivel
- Includes 21GU-SCS for attractive installation and protection of vehicles



Features



- SST construction and compatible with ISO 22241 Standard
- Converts nozzle from M34 threads to 1" BSPP
- Integral reconnectable breakaway 175-330 (lbs.) 80-150 (kg)
- Includes 21GU-BCS for attractive installation and protection of vehicles



21Gu Nozzle Adaptor Ordering Specifications

Product #	Description
21GU-SFH	DEF Stainless Steel Fixed Hose Inlet, 1" BSPP male
21GU-SSS	DEF Stainless Steel Swivel, 1" BSPP male
21GU-SSB	DEF Stainless Steel Reconnectable Breakaway / Swivel - NOTE: One (1) 21GU-SSB is required for each nozzle. Hose connection end is 1" BSPP male thread.
21GU-SCS	Replacement DEF Swivel Cover Sleeve (Comes with 21GU-SSS)
21GU-BCS	Replacement DEF Swivel/Breakaway Cover Sleeve (Comes with 21GU-SSB)

21Gu Mis-Filling Prevention Device

Product #	Description
MFPD	21GU Mis-Filling Prevention Device (MFPD). Order one MFPD or Bulk Packed for OEM sales (420 per case) NOTE: The MFPD is permanently installed in DEF tank fill pipe. Contact your vehicle supplier and specify the OPW DEF Mis-Filling Prevention Device.
MFPD-Pak	Retail Packaged Mis-Fill Prevention (Each)

Note: Want them individually packaged for retail? Contact OPW customer service at 1-800-422-2525.

OPW MIS-FILLING PREVENTION DEVICE (MFPD)

DEF mis-filling can be expensive. The OPW 21Gu MFPD offers the industry's most effective and affordable insurance policy against mis-filling mishaps actually stopping them before they happen. There is no better way to protect your

investment and the environment.