

## Advantages

- Capable of monitoring even the largest sites.
- Continuous inventory monitoring and tank testing through proven magnetostrictive probe technology.
- Highest rated continuous 24 hour leak detection (SCALD) in the industry.
- Density measurement and alarm capabilities.
- Patented AutoLearn™ electronic line leak detection capability, including Statistical Line Leak Detection for high throughput lines.
- Standard communication ports including one Ethernet and RS-485, two USB and RS-232.
- Complete web interface and email capabilities.
- Turbine Pump Interface, intelligent STP control.
- Programmable product colors.
- Programmable One Touch buttons.
- Quick Jump menu ease of navigation.
- F.A.S.T. programming with the Franklin Auto Setup Tool.

## TS-550 evo Fuel Management System

TS-550 evo brings a new level of usability and functionality to fuel management. A highly evolved user interface and blisteringly-fast new processor based on the proven TS-550 platform makes everything from daily functions to advanced setup and programming simple for every user.



### Specifications

- Number of tanks monitored: 12 (72\*)
- Number of lines monitored: 8 (48\*)
- Sensor input channels: 12 (72\*)
- Dry contact input channels: 2
- AC input channels: 12 (72\*)
- 4-20 ma input channels: 8 (48\*)
- Relay output channels: 2 (50\*)
- Display type: color LCD touch screen
- Printer type: thermal
- Internal audible alarm
- Alarm, warning and power LEDs
- Applicable liquids: petroleum, chemicals and hazardous waste
- Level units: inches, centimeters and millimeters
- Volume units: gallons or liters (mass with density option)
- Display size: 7" (17.78 cm)
- Power requirements: 110 to 240 VAC, 50/60 hz, 2.6 Amps
- Operating temperature: 32° to 104 °F (0° to 40 °C)
- Humidity: 0-90% non-condensing
- Dimensions: 11" x 11.75" x 9.5" (279 mm x 298 mm x 241 mm)
- Interface to devices with intrinsic safety rating:  
US - Class I, Div. I, Group D  
Europe - Group IIA, Zone 0

### Connectivity

- Ethernet/complete web interface
- RS-232/485
- USB
- Fax/data modem
- IFSF via Echelon

### Capabilities

- Inventory and delivery management
- Leak detection sensors
- Static and Continuous tank testing
- Static and Statistical Electronic Line Leak Detection
- High, low and water alarm set points
- Inventory reconciliation / tank autocalibration
- Density and mass measurement
- Secondary Containment Monitoring (vacuum)
- Turbine Pump Interface (TPI)
- Email notifications
- Back-up generator monitoring / fuel flow control

### Approvals

- UL, cUL, ATEX, IECEx
- Third party certification of leak detection capabilities

\* Maximum number when including additional options.

# Fuel Management System Consoles

## TS-550 evo

Model	Description
T550ED	TS-550 evo base console without printer
T550EDP	TS-550 evo base console with printer

## Expansion Console

Model	Description
EVO-EXPC	Secondary console to add eleven additional plug-in modules to the primary TS-550 evo console, comes without a display or printer

## TS-550 evo Console Hardware and Software Options

TS-550 evo consoles come standard with the ability to perform in-tank static leak detection. The following software and hardware options can be added to customize your console. The internal hardware options will be factory installed when ordered with the console.

### Internal Hardware Options

Part Number	Description
TS-DIMB	(I) Internal dispenser interface module, dispenser interface cable must be ordered separately
TS-LON	(E) EcheLON communication module, IFSF protocol capability
TS-MDMIB	(M) Internal modem, includes fax and data software capability

Note: Only one TS-DIM or TS-LON module can be installed per console.

### Internal Software Options

Part Number	Description
TS-TT	(T) Statistical Continuous Automatic Leak Detection, 24 hour continuous tank testing software
TS-TRAC	(R) Tank inventory reconciliation and auto calibration
TS-ELLD	(L) Electronic line leak detection
TS-SCM	(S) Secondary containment monitoring

## TS-550 evo Fuel Management System Console Ordering Guide

Console model, software and hardware options can be listed separately or combined when ordering. Systems shipped from the factory will list the combined part number. Complete console part numbers have a specific order and are created using the following guidelines:

**T550ED PM Y / TRL S**

### PM Y = Hardware Options

P = Printer

M = Internal modem

Y = I for dispenser interface module or E for a LON module

### TRL S = Software Options

T = SCALD 24-hour tank testing

R = Reconciliation/Autocalibration

L = Line leak detection

S = Secondary containment monitoring



franklinfueling.com

3760 Marsh Rd. • Madison, WI 53718, USA

Tel: +1 608 838 8786 • Fax: +1 608 838 6433

Tel: USA & Canada 1 800 225 9787 • Tel: Mexico 001 800 738 7610



FFS-0197 04-12