# **Pressure Vacuum Vent**

CIVACON's NV3000E high-flow pressure vacuum vent is designed for durability, safety and service performance.



NV3000E, Pressure Vacuum Vent

### **Features and Benefits**

- In accordance with EN14595
- Pressure Die-Cast aluminium design, stainless steel and acetal components for durability and longer life time
- Automatic sealing in case of a tanker rollover
- Pressure Flow capacity of 41 m³/h at 200 mbar
- Vacuum Flow capacity of 155 m<sup>3</sup>/h at 70 mbar
- **Lightweight** durable design (400 gram)
- **Removable** filter for easy serviceability
- Viton GFLT seals
- Quick-Strip-In-place design, no tools required
- Suitable for all Civacon 10" pressure activated fill-covers (PAF)
- **Double** dovetail grooves for poppet O-rings for a more secure and longer-lasting seal
- 11/4 BSPP connection

#### **Related products**

Art.	num	ber
тио	)-car	iac

**Description** Manhole cover assembly

## Spare parts

Article Nr.	Description
NV3000RK	Repair Kit NV3000E
Spare part only sup	oplied as complete kit

#### Contents Repair Kit NV3000RK


ltem	Article Nr.	Description	Qty
1	11745	Wave Spring	1
2	H71328	Vacuum Spring	2
3	H71329	Retaining Clip	2
4	H71330	Pressure Spring	2
5	9428	O-Ring 2-213 Viton A	1
6	11943	O-Ring 2-220 Viton A	2
7	6479	O-Ring 2-224 Buna-N	1
8	H71335	O-Ring 2-227 Viton A	1


### **Ordering specifications**


Art. numberDescriptionNV3000EPressure vacuum vent<br/>assembly (EN14595)


## **Specifications**

#### NV3000E, PRESSURE VACUUM VENT









Luid Transfer Group



# 0**]**W

#### 19