OPW Fluid Transfer Group Europe B.V. A DOVER COMPANY

Manifold order specification

1	On which site of the tank needs the manifold be mounted ?	☐ Left ☐ Right										
												
												

2		Manifold type:	No. of Campartments	Center to Center	Line Outlet	Seals	Sight	Return Spout	Return Spout Guard Bar	Return Spout Valve	API Guard Bar	End Connection Left	End Connection Right
	MF-	☐ 1=Single	☐ 1	☐ 1= 280 mm	☐ 0= Not applicable	☐ 1= Buna	☐ 0= N.A.	☐ 0= N.A.	☐ 0= N.A.	☐ 0= N.A. non-pneumatic	☐ 0= N.A.	☐ 1= End Cap	☐ 1= End Cap
		☐ 2=Double	☐ 2	☐ 2= 305mm	☐ 1= Open Tee	☐ 2= Viton	☐ 1= Sight Glass	☐ 1= BSPP Return Spout	☐ 1= Guard Bar		☐ 1= Guard Bar	☐ 2= 4"TW/TTMA Flanged	☐ 2= 4"TW/TTMA Flanged
			☐ 3	☐ 3= 250mm	☐ 2= TTMA Flanged			☐ 2= Return Spout w/ Couplings on all compartments		☐ 1= pneumatic			
			☐ 4	☐ 4= 355mm	☐ 3= 3"TW Flanged								
			☐ 5		☐ 4= 4"TTMA/TW Flanged 90°			☐ S= Special, return spout on compartments specified					
			☐ 6										
					Where ?			Where ?					
								If 1 or S::					
					☐ Left			☐ at compartiment.....					
					☐ Right								
					☐ In the middle								

EXAMPLE MF - 1 5 1 0 1 0 - 2 0 1 0 - 1 1

How to order - Use this example as your guide to determine the partnumber for the Manifold you require.